

MANTA WARRANTY OVERVIEW COVER CHART & FEE SCHEDULE



MANTA LIMITED WARRANTY OVERVIEW

Manta Roofing Products offers Limited Warranty durations of up to 25 years, as outlined in the table below, associated with MANTA 400 series acrylic and silicone system specs solutions:

	MANTA Limited Warranty on Materials	MANTA No Dollar Limit (NDL) Limited Warranty
Obtain	https://www.mantarroof.com/warranty.com	Customized warranty provided to the contractor
Coverage	Warranty covers manufacturing defects only for MANTA products.	The warranty covers leaks caused by manufacturing defects in MANTA products and workmanship.
Prorated Coverage	Yes	No
Warranty Fee	None	Yes, see table.
Contractor Requirement	None	Gold Star Liquid-Applied Roofing Contractor
Application Required	Registration Only: https://www.mantarroof.com/warranty.com	Yes

MANTA NDL LIMITED WARRANTY FEES

Warranty Duration	Warranty Fee (per square)			
	Silicone	Minimum Fee	Acrylic	Minimum Fee
10-years	\$8.00	\$8,00	\$6.00	\$600
15-years	\$10.00	\$1,000	\$8.00	\$800
20-years	\$12.00	\$1,200	n/a	n/a
25-years	\$14.00	\$1,400	n/a	n/a

MANTA WARRANTY OVERVIEW COVER CHART & FEE SCHEDULE



WARRANTY DURATION & SPECIFICATIONS

SPECIFICATION NOMENCLATURE

Coating Chemistry Abbreviation - First Letter of Substrate - # of Reinforcement Layers in Field - Gallons per Square

SILICONE MantaSil 430 Premium H.S. Coating Cover Chart

Assembly Configuration	Material Used	Granulated cap sheet	Smooth cap sheet/BUR (non-aggregate)	Aged or new SPF	Single-ply membrane (TPO/PVC/EPDM/)	Metal*
PREP	MANTACLEAN 101 CONDITIONER Diluted 5 to 1	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.
PRIMER 230	MANTAPRIME 230 BLEED BLOCK RIMER	Apply #230 Bleed Block Primer 1.00 gal per 100 sq. ft. 11 MIL DFT	Apply #230 Bleed Block Primer 1.00 gal per 100 sq. ft. 11 MIL DFT	n/a	Apply #230 Bleed Block Primer ON PVC 1.00 gal per 100 sq. ft. 9 MIL DFT	n/a
PRIMER 230	MANTAPRIME 235 MULTI PURPOSE PRIMER	n/a	n/a	n/a	Apply #235 Multipurpose Primer 1 gal per 100 sq. ft. 9 MIL DFT	Apply #235 Multipurpose Primer 0.75gal per 100 sq. ft.
SEAMS	MANTAFLASH 330 SILICONE H.S. MASTICS	Apply MantaFlash #330 Silicon Mastics on all field seams	Apply MantaFlash #330 Silicon Mastics on all field seams	Apply MantaFlash #330 Silicon Mastics on all field seams	Apply MantaFlash #330 Silicon Mastics on all field seams	Apply MantaFlash #330 Silicon Mastics on all field seams
FLASHING	MANTA POLYESTER 500 SERIES 4", 6", 12" 40"	Embed Reinforced fabric with Mantasil #430 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantasil #430 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantasil #430 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantasil #430 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantasil #430 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.

MANTSIL 430 Warranty Installation Options

10 YEAR	MANTSIL 430 1.5 GAL/SQR	Apply #430 1 coat 1.5 gal./sq. 22.5 mil DFT	Apply #430 1 coat 1.5 gal./sq. 22.5 mil DFT	Apply #430 1 coat 1.5 gal./sq. 22.5 mil DFT	Apply #430 1 coat 1.5 gal./sq. 22.5 mil DFT	Apply #430 1 coat 1.5 gal./sq. 22.5 mil DFT
15 YEAR	MANTSIL 430 2.0 GAL/SQR	Apply #430 1 coat 2.0 gal./sq. 30.0 mil DFT	Apply #430 1 coat 2.0 gal./sq. 30.0 mil DFT	Apply #430 1 coat 2.0 gal./sq. 30.0 mil DFT	Apply #430 1 coat 2.0 gal./sq. 30.0 mil DFT	Apply #430 1 coat 2.0 gal./sq. 30.0 mil DFT
20 YEAR	MANTSIL 430 2.5 GAL/SQR	Apply #430 1 coat 2.50 gal./sq. 37.5 mil DFT	Apply #430 1 coat 2.50 gal./sq. 37.5 mil DFT	Apply #430 1 coat 2.50 gal./sq. 37.5 mil DFT	Apply #430 1 coat 2.50 gal./sq. 37.5 mil DFT	Apply #430 1 coat 2.50 gal./sq. 37.5 mil DFT
25 YEAR	MANTSIL 430 3.0 GAL/SQR	Apply #430 1 coat 3.0 gal./sq. 45 mil DFT	Apply #430 1 coat 3.0 gal./sq. 45 mil DFT	Apply #430 1 coat 3.0 gal./sq. 45 mil DFT	Apply #430 1 coat 3.0 gal./sq. 45 mil DFT	Apply #430 1 coat 3.0 gal./sq. 45 mil DFT

MANTA WARRANTY

OVERVIEW COVER CHART & FEE SCHEDULE



ACRYLIC MantaAcrylic 400 Series Coating Cover Chart

Assembly Configuration	Material Used	Granulated cap sheet	Smooth cap sheet/BUR (non-aggregate)	Aged or new SPF	Single-ply membrane (TPO/PVC/EPDM/)	Metal*
PREP	MANTACLEAN 101 CONDITIONER Diluted 5 to 1	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.	Apply Manta #101 Roof Conditioner 1.00 gal. sq.
EMULSION 260	EMULSION #260	Apply Emulsion #260 6.00 gal per 100 sq. ft. 37.0 MIL DFT	Apply Emulsion #260 6.00 gal per 100 sq. ft. 37.0 MIL DFT	n/a	Apply Emulsion #260 6.00 gal per 100 sq. ft. 37.0 MIL DFT	n/a
FLASHING	Mantastic 318 Acrylic Roof Patch MantaPOLY 500 SERIES 4", 6", 12" 40"	Embed Reinforced fabric with Mantastic 318 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantastic 318 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantastic 318 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantastic 318 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.	Embed Reinforced fabric with Mantastic 318 in a 3-course method to reinforce all curbs, drains, waterways, ponding areas, etc.
REINFORCEMENT	MANTA POLYESTER 500 SERIES 40"	Acrylic with 6-gallon emulsion, one poly, 12-gallon of emulsion two poly Apply poly immediately after 6 gallons of emulsion	Acrylic with 6-gallon emulsion, one poly, 12-gallon of emulsion two poly Apply poly immediately after 6 gallons of emulsion	n/a	Acrylic with 6-gallon emulsion, one poly, 12-gallon of emulsion two poly Apply poly immediately after 6 gallons of emulsion	n/a

ACRYLIC EMULSION POLY 400 SERIES Warranty Installation Options

	Material Used	Granulated cap sheet	Smooth cap sheet/BUR (non-aggregate)	Aged or new SPF	Single-ply membrane (TPO/PVC/EPDM/)	Metal*
10 YEARS	6E-1P-3.0G410 Or 6E-1P-3.0G415 ~68.0 mil DFT	Apply EMULSION #260 (6) GAL/SQR + POLY Apply 2 Pass (3) gal total of 410 or 415 ~68.0 mil DFT	Apply EMULSION #260 (6) GAL/SQR + POLY Apply 2 Pass (3) gal total of 410 or 415 ~68.0 mil DFT	Apply EMULSION #260 (6) GAL/SQR + POLY Apply 2 Pass (3) gal total of 410 or 415 ~68.0 mil DFT	Apply EMULSION #260 (6) GAL/SQR + POLY Apply 2 Pass (3) gal total of 410 or 415 ~68.0 mil DFT	Apply EMULSION #260 (6) GAL/SQR + POLY Apply 2 Pass (3) gal total of 410 or 415 ~68.0 mil DFT
15 YEARS	12E-2P-4.0G415 ~120.0 mil DFT	Apply 2 pass EMULSION #260 (6) GAL/SQR + POLY each pass. Apply 2 Pass (4) gal total of ~120.0 mil DFT	Apply 2 pass EMULSION #260 (6) GAL/SQR + POLY each pass. Apply 2 Pass (4) gal total of ~120.0 mil DFT	Apply 2 pass EMULSION #260 (6) GAL/SQR + POLY each pass. Apply 2 Pass (4) gal total of ~120.0 mil DFT	Apply 2 pass EMULSION #260 (6) GAL/SQR + POLY each pass. Apply 2 Pass (4) gal total of ~120.0 mil DFT	Apply 2 pass EMULSION #260 (6) GAL/SQR + POLY each pass. Apply 2 Pass (4) gal total of ~120.0 mil DFT

ALL ACRYLIC POLY 400 SERIES Warranty Installation Options

10 YEARS	1PLY-4.5 G410 or 1PLY-4.5 G415 ~36 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon 36 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon 36 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon 36 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon 36 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon 36 mil DFT
15 YEARS	2PLY-6.0 G415 ~45.5 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon Apply 1 pass 2.0 gallon ~45.5 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon Apply 1 pass 2.0 gallon ~45.5 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon Apply 1 pass 2.0 gallon ~45.5 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon Apply 1 pass 2.0 gallon ~45.5 mil DFT	Apply 1 pass 2.5 gals + poly Apply 1 pass 2.0 gallon Apply 1 pass 2.0 gallon ~45.5 mil DFT

MANTA WARRANTY OVERVIEW COVER CHART & FEE SCHEDULE



MANTA LIMITED WARRANTY PROTOCOL

	MANTA Limited Warranty on Materials	MANTA NDL Limited Warranty
Before Work Commencing:		
Submit MANTA Limited Warranty Registration	Required Register at https://www.mantarooft.com/warranty	n/a
Secure Master Craftsman Liquid-Applied Roofing (contact your local rep for credential details) ³	n/a	Required
Submit MANTA Limited Warranty Application including;	n/a	Required
Six pre-work photos of the field, areas in need of repair, and any unusual flashing details, plus;	n/a	Required
Submit the MANTA Adhesion Test form;	n/a	Required ²
At MANTA's discretion, a core sample may be required.	n/a	Pending Application Review
Infrared or Nuclear Moisture Scan	n/a	Required
During Work:		
Save all receipts for products purchased;	Recommended	Required
Document work-in-progress including: – Two (2) photos (min) of the field indicating the surface was properly cleaned and prepared – Two (2) photos (min) of each stage of work as specified (seams, fasteners, primer, each coating layer, reinforcement, etc.)	Recommended	Required
Upon Completion of Work:		
Submit receipts of MANTA products purchased.	Submission is not required; MANTA recommends that the contractor/building owner maintains records to support in the event of a claim.	Required
Submit all notes and work-in-progress photos.		Required
Submit six (6) photos of the completed project taken from the same vantage point as pre-work photos.		Required
A MANTA representative must inspect the completed project.	At MANTA's Discretion	Required

Contractors shall submit all forms and photographs to
<https://www.mantarooft.com/warranty>